



Teraflux™ AT1500

The Auradine Teraflux portfolio of Bitcoin miners offers industry-leading performance, quality, uptime, security, and demand response features to deliver the lowest total cost of ownership for Bitcoin mining solutions.

The [Auradine Teraflux AT1500](#) is an ASIC-based air-cooled Bitcoin miner. Miners can be managed using APIs and a web console that is available for each miner, and with FluxVision™ (purchased separately), the cloud management solution for pre-deployment configuration and tuning of Auradine miners at scale.

Uptime

Auradine Bitcoin miners possess exceptional uptime performance due to several key attributes that ensure reliability and better financial outcomes for Bitcoin mining operations.

- **Superior Build Quality** — High-quality components and construction reduce the likelihood of common failure modes seen in traditional systems. This is crucial for reliably maintaining continuous operation and avoiding downtime.
- **Wide Operating Temperature Range** — Bitcoin mining operations often take place in various environments with different temperatures. A wider operating temperature range allows the miners to function effectively even in extreme conditions, preventing unexpected shutdowns.
- **Demand Response Capabilities** — The ability to seamlessly adjust the operating point on the performance-power spectrum enables the miners to slow down and keep running, instead of shutting down completely. Unlike traditional Bitcoin miners that take ten minutes per iteration and require frequent reboots to adjust the operating frequencies and voltages of the mining ASICs, the Auradine miners have a sophisticated, built-in Dynamic Frequency and Voltage Scaling (DVFS) mechanism that perform these optimizations in half the time. To maximize profitability and minimize downtime, operators can respond to the time-based rates or signals from the electric grid and adjust power consumption during peak periods, and promptly resume desired hashing levels thereafter.

Software Specifications

AutoTune™

Using energy cost, Bitcoin price, Bitcoin reward, Bitcoin mining difficulty, and a characterization of historical miner operation continually revised through machine learning, AutoTune calculates the optimal TH/s required to maximize profitability. AutoTune is available with FluxVision.

EnergyTune™

EnergyTune uses Dynamic Voltage and Frequency Scaling (DVFS) to set the desired power consumption (in Joules) per miner by suitably varying all other system parameters. In addition to this default mode where you can customize your preference, the web console on the miner also allows the operator to select an operating mode of ECO (least power consumed per TH or maximum efficiency) or Turbo (highest TH/s performance). EnergyTune is configurable using APIs and the web console that is available for each miner.

AutoTemp

Temperature regulating mechanism that continuously monitors the internal junction temperature of the ASICs and reduces the TH/s to ensure that the ASICs are operating in a safe zone. AutoTemp is enabled on every miner and automatically tuned to a pre-determined threshold to dial down performance and prevent damage from overheating.

Hardware-Based Secure Boot

The Teraflux portfolio of miners are equipped with a hardware-based root of trust secure boot implementation that ensures the integrity of the software during boot up. The secure boot process validates that only digitally signed and trusted code is allowed to run during the boot sequence and thereby safeguards the miner from the execution of unauthorized or potentially malicious code.

User-friendly Interface and API Support

The miners support a user-friendly web-based console and a set of APIs, as well as FluxVision, the cloud management solution. The dashboard on the miner web console displays system information and statistics on memory consumption, hash rate, power consumption and efficiency with additional details on frequency, voltage, and temperature for each installed hashboard. It also makes it very easy to install and upgrade Auradine firmware on the miner.

You can also leverage the API integration with Foreman or AwesomeMiner for fleet management.

FluxVision™

FluxVision is the cloud management solution for pre-deployment configuration and tuning of Auradine miners at scale. It is a standalone product that helps Bitcoin operators organize miners as 'miner groups' to simplify the configuration and reporting for different sets of miners, and leverage Zero Touch Provisioning (ZTP) so that the miners can start hashing as soon as they are plugged into the network.

FluxGPT

On FluxVision, you can also leverage FluxGPT, the generative AI-based conversational experience that's designed to assist you in finding answers or information on Auradine products quickly and efficiently.

Hardware Specifications

AT1500 Product Specifications	Value
Crypto Algorithm	SHA-256
Optimal Power Efficiency (Joules/TH)	16 ¹
Hashing Performance (TH/s at Joules/TH)	0-260 / xx Joules/TH at xxx TH/s ¹
Operating Temperature Range	-4 to 122°F (-20 to 50°C ²)
Power Supply	5000 Watts ³ , 2 x C20 Input
Power Cables Included	2 x C19 to C20
Cooling Mechanism	Air-cooled
Power Supply AC Input Voltage, Nominal, Min/Max	200-240V, 180 - 264V
Power Supply AC Input Frequency	48-62 Hz
Power Supply AC Input Current	0-17.6 Amp per input
Connectivity Options	RJ45 Ethernet 10/100/1000
Dimensions (Length/Width/Height)	15.5 x 8 x 11.5 inches / 395 x 202 x 290mm
Weight	38.6-42.5lbs / 17.5-19.3kg ⁴
Storage Temperature	-40 to 158°F (-40 to 70°C)
Operation Humidity, RH	20-80% RH non-condensing
Operation Altitude	9,840ft (3,000M) ⁵

¹ ±8%

² At sea level

³ PSU spec; system maximum may be slightly lower

⁴ Depends on specific power supply unit shipped with device

⁵ Operating temperature will vary based on altitude

© 2023 Auradine, Inc. All rights reserved. For informational use only. Auradine, the Auradine logo, AutoTune, EnergyTune, FluxVision, FluxGPT and other Auradine marks are either registered trademarks or trademarks of Auradine, Inc. in the United States and/or other countries. Other names and brands may be claimed as the property of others. Reference to specific trade names, trademarks, or otherwise, does not necessarily constitute or imply its endorsement or recommendation by Auradine. Other names and brands may be claimed as the property of others.

For more information, visit auradine.com or contact us at info@auradine.com.

Auradine Inc.
3200 Coronado Drive,
Santa Clara, CA 95054